

AWL 55 FR

AUTOMATED FLUX RECOVERY UNIT



Key Attributes

- Portable Unit
- Recovers all unused flux
- Greatly reduces clean-up time
- Creates a safer, healthier work environment
- Light weight, compact and portable for easy handling
- Fused slag is automatically separated from unused slag.

AWL 55 FR

AUTOMATED FLUX RECOVERY UNIT

TECHNICAL SPECIFICATIONS

PARAMETERS	VALUE	UNIT
VOLTAGE	415, +15%, -10%	VOLTS AC
PHASE	3	NO
FREQUENCY	50/60	HZ
VACUUM PRODUCER	5	MULTISTAGE TURBINES (NO)
VACUUM	2500	MM / WG
ELECTRIC MOTOR	3	HP
STARTER	DOL	TYPE
DRIVE	BELT	TYPE
FILTER	DUAL STRAIN FILTER BAG	TYPE
FLUX RECOVERY HOSE	25 MM X 5 M	DIA. X LENGTH
FLUX HOPPER CAPACITY	45	LITRES
DIMENSIONS		
LENGTH	1600	MM
WIDTH	570	MM
HEIGHT	850	MM
WEIGHT	95	KG

ORDERING INFORMATION

INFORMATION	MODEL	PRODUCT CODE
FLUX RECOVERY UNIT	AWL-55FR	F10.36.004.0058

WARRANTY DETAILS

Duration: One year from the commissioning date. ADOR WELDING LIMITED ensures new equipment sold through Plant/Area Offices/Authorized Distributors is free from defects in materials and workmanship, performing as per applicable specifications.

Cable Wear Disclaimer: ADOR is not liable for cable wear or consequential damage caused by flexing and abrasion. End users are responsible for regularly inspecting cables for wear and addressing issues before cable failure occurs.

Design and Specification Changes: ADOR WELDING LIMITED reserves the right to modify designs and specifications without prior notice due to continuous development.

Customer Care: Supported by a dedicated customer care package.



ADOR WELDING LIMITED

Ador International, Jebel Ali Free Zone Authority (JAFZA) at Dubai, UAE

+971 4320 1176 | awloverseas@adorians.com



www.adorwelding.com