*

BENCH POSITIONER

100 KC



Key Attributes

- · 100 kg capacity.
- · Ideal for small parts like flanges and pipes.
- · Includes a chuck for 8 to 10" self-centering.
- · Manual tilting from 0 to 90°.
- · Built-in pendant with Forward-Stop-Reverse and speed control.
- · High-frequency protection.
- · Foot switch included.
- · Hollow bore positioner up to 200 mm available on request.
- Suitable for light-duty applications like flange assembly, painting, polishing, and grinding.

BENCH POSITIONER

Technical Specifications

MODEL TR-100	SPECIFICATIONS
CAPACITY	100 KG CAPACITY IN ALL DIRECTION
TILTING	0 TO 90°, MANUAL TILTING
FACE PLATE DIAMETER	300 MM
FACE PLATE SPEED	0.45 TO 8 RPM
WEIGHT	APPROX 40 KG.
POWER INPUT	3 PHASE AC / 1 PHASE AC, 50 / 60HZ

WARRANTY DETAILS

Duration: One year from the commissioning date. ADOR WELDING LIMITED ensures new equipment sold through Plant/Area Offices/Authorized Distributors is free from defects in materials and workmanship, performing as per applicable specifications.

Cable Wear: ADOR is not liable for wear and damage to cables caused by flexing and abrasion. Users must regularly inspect cables for wear and address any issues before cable failure occurs.

Design and Specification Changes: ADOR WELDING LIMITED reserves the right to modify designs and specifications without prior notice due to continuous development.

Customer Care: Supported by a dedicated customer care package.



ADOR WELDING LIMITED

Corporate Marketing Office: Survey No.147 / 2B+3, Near Khandoba Mandir, Akurdi Chowk, Chinchwad, Pune - 411019. Maharashtra. India.



