



FRU - 33 / 55

PORTABLE FLUX RECOVERY UNIT



Key Attributes

- Portable Unit
- Recovers all unused flux
- Greatly reduces clean-up time
- Creates a safer, healthier work environment
- Light weight, compact and portable for easy handling
- Fused slag is automatically separated from unused slag.

FRU - 33 / 55

PORTABLE FLUX RECOVERY UNIT

Technical Specifications

PARAMETERS	FRU-33	FRU-55	UNIT
VOLTAGE	415, +15%, -10%	415, +15%, -10%	VOLTS AC
PHASE	3	3	NO
FREQUENCY	50/60	50/60	HZ
VACUUM PRODUCER	MULTISTAGE TURBINES	MULTISTAGE TURBINES	-
VACUUM	1500	2500	MM / WG
ELECTRIC MOTOR	3	5	HP
STARTER	DOL	DOL	TYPE
DRIVE	BELT	BELT	TYPE
FILTER	DUAL STRAIN FILTER BAG	DUAL STRAIN FILTER BAG	TYPE
FLUX RECOVERY HOSE	38 MM X 5 M	38 MM X 5 M	DIA. X LENGTH
FLUX HOPPER CAPACITY	30	45	LITRES
DIMENSIONS			
LENGTH	1600	1600	MM
WIDTH	570	570	MM
HEIGHT	850	850	MM
WEIGHT	95	95	KG

ORDERING INFORMATION

INFORMATION	MODEL	PRODUCT CODE
FLUX RECOVERY UNIT	FRU - 33 (50 Hz)	F89.32.202.0933
FLUX RECOVERY UNIT	FRU - 33 (60 Hz)	F89.32.202.0847
FLUX RECOVERY UNIT	FRU - 55 (50 Hz)	F89.32.202.0932
FLUX RECOVERY UNIT	FRU - 55 (60 Hz)	F89.32.202.0845

WARRANTY DETAILS

Duration: One year from the commissioning date. ADOR WELDING LIMITED ensures new equipment sold through Plant/Area Offices/Authorized Distributors is free from defects in materials and workmanship, performing as per applicable specifications.

Cable Wear: ADOR is not liable for wear and damage to cables caused by flexing and abrasion. Users must regularly inspect cables for wear and address any issues before cable failure occurs.

Design and Specification Changes: ADOR WELDING LIMITED reserves the right to modify designs and specifications without prior notice due to continuous development.

Customer Care: Supported by a dedicated customer care package.



ADOR WELDING LIMITED

Corporate Marketing Office: Survey No.147 / 2B+3, Near Khandoba Mandir, Akurdi Chowk, Chinchwad, Pune - 411019. Maharashtra. India.

☎ 1800 233 1071 ✉ cmo@adorians.com 📞 +91 20 40706000

