*

TR-TURNING ROTATORS

PORTABLE, 1,000 KG CAPACITY



Key Attributes

- · 1,000 Kg capacity.
- · For rotating pipes or vessels.
- · Metallic rollers with polyurethane coating.
- · Quick, accurate roll centering adjustment.
- · Built-in pendant with Forward-Stop-Reverse and speed control.
- · High-frequency protection.
- · Optional foot switch.

TR-TURNING ROTATORS

PORTABLE, 1,000 KG CAPACITY

Technical Specifications

MODEL TR-1000	SPECIFICATIONS
POWER INPUT	3 PHASE AC / 1 PHASE AC, 50/60HZ
DIAMETER RANGE (D)	MIN 100 MM - MAX 800 MM (MIN 4" - MAX 32")
SURFACE SPEED RANGE	200 - 1500 MM / MIN (8 IPM - 58 IPM)
ROLLER MATERIAL	PU
LOAD CAPACITY	1000 KG.
PU ROLLER DIAMETER / WIDTH	200 MM (8") / 50 MM (2")
JOB DIAMETER ADJUSTMENT	MANUAL ADJUSTMENT OF ROLLERS IN THE GIVEN SLOTS / HOLES

WARRANTY DETAILS

Duration: One year from the commissioning date. ADOR WELDING LIMITED ensures new equipment sold through Plant/Area Offices/Authorized Distributors is free from defects in materials and workmanship, performing as per applicable specifications.

Cable Wear Disclaimer: ADOR is not liable for cable wear or consequential damage caused by flexing and abrasion. End users are responsible for regularly inspecting cables for wear and addressing issues before cable failure occurs.

Design and Specification Changes: ADOR WELDING LIMITED reserves the right to modify designs and specifications without prior notice due to continuous development.

Customer Care: Supported by a dedicated customer care package.



ADOR WELDING LIMITED

Ador International, Jebel Ali Free Zone Authority (JAFZA) at Dubai, UAE



