



OPTIONAL ACCESSORIES

WELDING TRANSFORMERS RED 400 (S) / 403 / 503 / 603, TPA 403:

- Welding cables with Electrode Holder, Earthing cable with Earth clamp (50 mm² / 70 mm²). Lengths – 5 Meter / 10 Meter.

THYROLUXE 401 / 600 / 1000 / 1200; GL 601;

- Welding cables with Electrode Holder, Earthing cable with Earth clamp (50 mm² for THYROLUXE 401; 70 mm² for THYROLUXE 600; 95 mm² for THYROLUXE 1000 and 1200; 70 mm² for GL 601). Lengths – 5 Meter / 10 Meter.
- In-built VRD Unit.
- RCCB (for THYROLUXE 401 / 600 only).
- Gouging Torch models CAG 9 / CAG 15 (with GL 601, THYROLUXE 100, THYROLUXE 1200 only)

SUPERGEN 320:

- Welding cables with Electrode Holder, Earthing cable with Earth clamp (50 mm² / 70 mm²). Lengths – 5 Meter / 10 Meter.

SILENT CHALLENGER 401 / 501 / 2 X 301:

- Welding cables with Electrode Holder, Earthing cable with Earth clamp (50 mm² / 70 mm²). Lengths – 5 Meter / 10 Meter.
- Digital Engine Control Panel with Auto shut off (SC 401 / 501 only)
- DPAV Meters
- Spark Arrestor
- Two-wheel undercarriage with Leaf spring and / or Parking brake arrangement.

CHAMP 250, CHAMP 250 X, CHAMP T 400, CHAMP 400 X, CHAMP 600, CHAMP 1200:

- Remote Control Unit (standard 10-meter Length) for CHAMP 250 / CHAMP T 400 / other CHAMP Series machines which do not have Remote Control Unit in standard supply scope. Extended lengths of Remote-Control units with 5 meter increments up to 50-meter length can be offered for CHAMP T 400 and CHAMP 600.
- Welding cables with Electrode Holder, Earthing cable with Earth clamp (25 mm² for CHAMP 250 / CHAMP 250 X; 50 mm² for CHAMP T 400 / CHAMP 400 X; 70 mm² for CHAMP 600; 95 mm² for CHAMP 1200. Lengths – 5 Meter / 10 Meter.
- In-built VRD Unit – for CHAMP 250, CHAMP T 400, CHAMP 600, CHAMP 1200 only
- RCCB (CHAMP T 400 and CHAMP 600).
- Gouging Torch models CAG 9 / CAG 15 (with CHAMP 600 / 1200 only).

CHAMPTIG 300 P / 400 P / 400 AD / 500 AD

- Handheld or Foot Controlled Remote Unit – 10-meter length.
- Welding cables with Electrode Holder, (50 mm² / 70 mm²). Lengths – 5 Meter / 10 Meter.
- RCCB.



OPTIONAL ACCESSORIES

MAXIMIG 251 / 400 / 600, STRIKER 400, CHAMPMIG 250 / 400 / 500 / 600. CHAMPMIG 400 CC-CV, CHAMPMULTI 400/600, CHAMP PULSE 500.

- Power Source – Wire feeder Interconnection cable of alternate lengths (in 5-meter increments) – up to 10 meter for MAXIMIG 251 / CHAMPMIG 250, up to 15 meter for CHAMPMIG 400 / CHAMPMULTI 400 / CHAMPMIG 400 CC-CV, up to 20 meter for CHAMPMIG 500 / CHAMPMULTI 600 / CHAMP PULSE 500.
- Earthing cable with Earth clamp (25 mm² for MAXIMIG 250 / CHAMPMIG 250; 50 mm² for CHAMPMIG 400 / CHAMP MULTI 400; 70 mm² for CHAMPMIG 500 / CHAMPMULTI 600 / CHAMP PULSE 500; Lengths – 5 Meter / 10 Meter.
- Gas Preheater with 3-meter cable and suitable plug – 110 V (for use with CO₂ Shielding Gas)
- Single stage Gas Regulator with Flow gauge – Argon Regulator / CO₂ Regulator
- RCCB – with CHAMPMIG 400 / CHAMP MULTI 400 only.

MAESTRO series SAW Equipments:

- Welding cable and Earthing cable assemblies – 70 mm² twin parallel / 95 mm² twin parallel with connecting lugs at both ends (for Welding Cable) and connecting lug + Heavy duty Earthing clamp (for Earthing cable) – different lengths in increments of 5 meter up to 25 meter.
- Power Source to Welding Head controller control interconnection cable (standard scope – 10 meter) additional lengths in increments of 5 meters up to 20 meters.